


3%" Ø Lag screw or bolt with nut/washer



DIST COUNTY POST MILES SHEET TOTAL TOTAL PROJECT NO. SHEETS REGISTERED CIVIL ENGINEER , Jeffrey B. Woo May 1, 2006 C41260 PLANS APPROVAL DATE Exp. 3-31-07 The State of California or its officers or agents shall not be responsible for the accuracy or completeness of electronic copies of this pla To get to the Caltrans web site, go to: http://www.dot.ca.gov

TYPE B PANEL 21/2" Thick Length

TABLE

5'-0" 15'-6" to 16'-6" 4'-6" 15'-6" to 18'-6" 4'-0" 15'-6" to 20'-6" 3'-6" 15'-6" to 23'-6" 3'-0" 15'-6" to 24'-0" 2'-6" 15'-6" to 24'-0" 2'-0" 15'-6" to 24'-0" 1'-6" 15'-6" to 24'-0"

See Note 4

SECTION B-B

NOTES:

- 1. See Standard Plan S85 for post spacing table.
- 2. See Standard Plan S86 for extrusion details.
- 3. All horizontal extrusions shall be continuous.
- 4. Depth and length of panel shall be graduated in increments of 6".
- 5. For multiple panel signs, see Standard Plan S85 for seam closure extrusion quantities.
- 6. Extrusions shall be joined as specified in the Special Provisions.

STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION

ROADSIDE LAMINATED SIGN SINGLE OR MULTIPLE PANEL TYPE B (2½" THICK)

NO SCALE

S83

Channel edge Honeycomb core May be notched to clear router Vertical tube spacer 0.040" Aluminum base sheet Wood post

SECTION A-A

Face

0.063" Aluminum base sheet

Ň

